

2000 TOW RATINGS

Compiled by Doug Marion

Trailer Life's annual guide to factory tow ratings for autos, light-duty trucks, sport-utility vehicles and vans is the largest guide ever published. Minimum vehicle towing capacity is 2,000 pounds. While the respective manufacturers provide all the specifications—and every effort has been taken to ensure accuracy—buyers should verify the information by reading the factory tow guide for their particular vehicle. It's also important to note that some capacities may change during the model year without notice, and a few were not available at presstime. Again, consult with the latest towing guide for your respective vehicle manufacturer before signing on the dotted line.

AM GENERAL

Vehicle	Engine	Tow Limit (lbs.)
Hummer 2dr Hardtop	6.5 TD	8,300
Hummer 4dr Open Top	6.5 TD	8,050
Hummer 4dr Hardtop	6.5 TD	7,900
Hummer Station Wagon	6.5 TD	7,710

TD = Turbodiesel

CADILLAC

Vehicle	Engine	Tow Limit (lbs.)
Deville	4600 V-8	3,000a
Seville	4600 V-8	3,000a
Escalade	5700 V-8	6,600a

aRequires trailer-towing package.

CHEVROLET/GMC

Vehicle	Engine	Tow Limit (lbs.)
Astro/Safari RWD	4300 V-6	5,100a,h
Astro/Safari RWD	4300 V-6	5,600b,h
Astro/Safari RWD	4300 V-6	6,100c,h
Astro/Safari AWD	4300 V-6	5,300b,h
Astro/Safari AWD	4300 V-6	5,800c,h
Express/Savana G1500	4300 V-6	4,900b
Express/Savana G1500	4300 V-6	5,400c,h
Express/Savana G2500	4300 V-6	4,700b
Express/Savana G2500	4300 V-6	5,400d,h
Express/Savana G1500	5000 V-8	5,800b,h
Express/Savana G2500	5000 V-8	5,600b,h
Express/Savana G1500	5700 V-8	6,300b,h
Express/Savana G1500	5700 V-8	7,300c,h
Express/Savana G2500	5700 V-8	6,100b,h
Express/Savana G2500	5700 V-8	7,100c,h
Express/Savana G2500	5700 V-8	8,300d,h
Express/Savana G3500	5700 V-8	6,600c,h
Express/Savana G3500	5700 V-8	8,100d,h
Express/Savana G2500	6.5 TD	8,900c/d,h
Express/Savana G3500	6.5 TD	8,800c/d,h
Express/Savana G3500	7400 V-8	7,900b,h
Express/Savana G3500	7400 V-8	9,400c,h
Express/Savana G3500	7400 V-8	10,000d,h
Blazer/Jimmy	4300 V-6	4,900e,f
Blazer/Jimmy	4300 V-6	5,900b,f,h
Blazer/Jimmy	4300 V-6	4,400b,g
Blazer/Jimmy 4WD	4300 V-6	4,600e,f
Blazer/Jimmy 4WD	4300 V-6	5,600b/c,f,h
Blazer/Jimmy 4WD	4300 V-6	4,000b,g
Blazer/Jimmy 4WD	4300 V-6	4,500c,g
S-10/Sonoma	2200 I-4	2,000c,g
S-10/Sonoma	2200 I-4	2,300d,g
S-10/Sonoma	2200 I-4	3,200d,f
S-10/Sonoma	4300 V-6	5,400e,f,h
S-10/Sonoma	4300 V-6	6,400b,f,h
S-10/Sonoma 4WD	4300 V-6	4,900e,f
S-10/Sonoma 4WD	4300 V-6	5,900b/c,f,h
S-10/Sonoma	4300 V-6	4,200e,g
S-10/Sonoma 4WD	4300 V-6	3,900e,g
S-10/Sonoma 4WD	4300 V-6	4,400b,g
S-10/Sonoma 4WD	4300 V-6	4,900c,g
Silverado/Sierra 1500	4300 V-6	3,900e,g
Silverado/Sierra 1500	4300 V-6	4,400b,g
Silverado/Sierra 1500	4300 V-6	4,900e,f
Silverado/Sierra 1500	4300 V-6	5,400b,f,h
Silverado/Sierra 1500	4300 V-6	5,900c,f,h
Silverado/Sierra 1500 4WD	4300 V-6	5,100b,f,h
Silverado/Sierra 1500 4WD	4300 V-6	5,600c,f,h
Silverado/Sierra 1500 4WD	4300 V-6	4,100b,g
Silverado/Sierra 1500 4WD	4300 V-6	4,600c,g
Silverado/Sierra 1500	4800 V-8	4,800b,g
Silverado/Sierra 1500	4800 V-8	6,800b,f,h
Silverado/Sierra 1500	4800 V-8	5,800c,g,h
Silverado/Sierra 1500	4800 V-8	7,800c,f,h
Silverado/Sierra 1500 4WD	4800 V-8	5,500c,g,h
Silverado/Sierra 1500 4WD	4800 V-8	7,500c,f,h
Silverado/Sierra 1500 4WD	4800 V-8	6,500d,g,h
Silverado/Sierra 1500 4WD	4800 V-8	8,500d,f,h
Silverado/Sierra 1500	5300 V-8	7,800b,f,h
Silverado/Sierra 1500	5300 V-8	8,800c,f,h
Silverado/Sierra 1500 4WD	5300 V-8	8,500c,f,h
Silverado/Sierra 1500 4WD	5300 V-8	9,500d,f,h
Silverado/Sierra 2500 LD	5300 V-8	7,400b,f,h
Silverado/Sierra 2500 LD	5300 V-8	8,400c,f,h
Silverado/Sierra 2500 LD	5300 V-8	9,400d,f,h

Silverado/Sierra 2500 LD	6000 V-8	9,200c,f,h
Silverado/Sierra 2500 LD	6000 V-8	11,200d,h,i
Silverado/Sierra 2500 HD	6000 V-8	9,200c,h,i
Silverado/Sierra 2500 HD 4WD	6000 V-8	8,800c,h,i
Silverado/Sierra 2500 HD 4WD	6000 V-8	10,800d,h,i

C/K Classic Sierra, Conventional Towing:

2500	5700 V-8	7,100c,h,i
2500	5700 V-8	8,600d,h,i
2500 4WD	5700 V-8	6,800c,h,i
2500 4WD	5700 V-8	8,300d,h,i
2500	6.5 TD	9,300c/d,h,i
2500 4WD	6.5 TD	9,000c/d,h,i
2500	7400 V-8	9,900c,h,i
2500	7400 V-8	10,000d,h,i
2500 4WD	7400 V-8	9,500c,h,i
2500 4WD	7400 V-8	10,000d,h,i
3500	5700 V-8	8,600d,h,i
3500	5700 V-8	10,000h,i,j
3500 4WD	5700 V-8	8,300d,h,i
3500	6.5 TD	9,300d,h,i
3500 4WD	6.5 TD	9,000d,h,i
3500 HD	6.5 TD	10,000h,i,k
3500 Chassis Cab	6.5 TD	10,000h,i,l
3500	7400 V-8	10,000d,h,i
3500	7400 V-8	10,000j,h,i
3500 4WD	7400 V-8	10,000d,h,i
3500 4WD Chassis Cab	7400 V-8	10,000h,i,k/l

C/K, Classic Sierra, Fifth-Wheel Towing:

2500	5700 V-8	7,100c,i
2500	5700 V-8	8,600d,i
2500 4WD	5700 V-8	6,800c,i
2500 4WD	5700 V-8	8,300d,i
2500	6.5 TD	9,300c/d,i
2500 4WD	6.5 TD	9,000c/d,i
2500	7400 V-8	9,900c,i
2500	7400 V-8	11,900d,i
2500 4WD	7400 V-8	9,500c,i
2500 4WD	7400 V-8	11,500d,i
3500	5700 V-8	8,600d,i
3500	5700 V-8	10,000j,i
3500 4WD	5700 V-8	8,300d,i
3500	6.5 TD	9,300d,i
3500 4WD	6.5 TD	9,000d,i
3500 HD	6.5 TD	11,000k/l,i
3500	7400 V-8	11,800d,i
3500	7400 V-8	13,800j,i
3500 4WD	7400 V-8	11,500d,i
3500 4WD	7400 V-8	13,500j,i
3500 HD Chassis Cab	7400 V-8	13,000k/l,i
Tahoe/Yukon 1500	4800 V-8	6,100b,f,h
Tahoe/Yukon 1500	4800 V-8	7,100c,f,h
Tahoe/Yukon 1500 4WD	4800 V-8	6,800b,f,h
Tahoe/Yukon 1500 4WD	4800 V-8	7,800d,f,h
Tahoe/Yukon 1500	5300 V-8	7,100b,f,h
Tahoe/Yukon 1500	5300 V-8	8,100c,f,h
Tahoe/Yukon 1500 4WD	5300 V-8	7,800b,f,h
Tahoe/Yukon 1500 4WD	5300 V-8	8,800d,f,h
Yukon Denali	5700 V-8	6,600c,f,h
Suburban/Yukon XL 1500	5300 V-8	8,000c,f,h
Suburban/Yukon XL 1500	5300 V-8	9,000d,f,h
Suburban/Yukon XL 1500 4WD	5300 V-8	7,800b,f,h
Suburban/Yukon XL 1500 4WD	5300 V-8	8,800d,f,h
Suburban/Yukon XL 2500	6000 V-8	8,500b,f,h
Suburban/Yukon XL 2500	6000 V-8	10,500d,f,h
Suburban/Yukon XL 2500 4WD	6000 V-8	8,100b,f,h
Suburban/Yukon XL 2500 4WD	6000 V-8	10,100d,f,h
Venture	3400 V-6	3,500h

LD = Light Duty HD = Heavy Duty TD = Turbodiesel

aRequires 3.23:1 axle ratio.

bRequires 3.42:1 axle ratio.

cRequires 3.73:1 axle ratio.

dRequires 4.10:1 axle ratio.

eRequires 3.08:1 axle ratio.

fRequires automatic transmission.

gRequires manual transmission.

hRequires heavy-duty tow package.

iRequires automatic or manual transmission.

jRequires 4.56:1 axle ratio.

kRequires 4.63:1 axle ratio.

lRequires 5.13:1 axle ratio.

CHRYSLER

Vehicle	Engine	Tow Limit (lbs.)
Concorde, 300M, LHS	3.2 V-6	2,000a
300M, LHS	3.5 V-6	2,000a
Town & Country Van	3.3, 3.8 V-6	3,500a,b

aRequires trailer-towing package.

bRequires a Class II load-equalizing hitch.

DODGE

Vehicle	Engine	Tow Limit (lbs.)
Dakota	2.5 I-4	2,250a,g
Dakota	3.9 V-6	5,050b,d
Dakota	3.9 V-6	4,300d,g
Dakota	3.9 V-6	5,450a,b
Dakota	3.9 V-6	8,900b,f
Dakota	4.7 V-8	5,600d,g
Dakota	4.7 V-8	6,600a,g
Dakota	4.7 V-8	5,250c,d
Dakota	4.7 V-8	6,550a,c
Dakota R/T	5.9 V-8	2,000a,b
Dakota R/T Club Cab	5.9 V-8	2,000a,b
Dakota 4WD	3.9 V-6	4,000d,g
Dakota 4WD	3.9 V-6	4,800a,g
Dakota 4WD	3.9 V-6	5,200a,b
Dakota 4WD	4.7 V-8	5,400d,g
Dakota 4WD	4.7 V-8	6,400a,g
Dakota 4WD	4.7 V-8	6,350a,b
Dakota 4WD	4.7 V-8	5,050b,d
Dakota Club Cab	2.5 I-4	2,050a,g
Dakota Club Cab	3.9 V-6	3,550g,h
Dakota Club Cab	3.9 V-6	4,050d,g
Dakota Club Cab	3.9 V-6	4,850a,g
Dakota Club Cab	3.9 V-6	4,800b,d
Dakota Club Cab	3.9 V-6	5,200a,b
Dakota Club Cab	4.7 V-8	5,500d,g
Dakota Club Cab	4.7 V-8	6,500a,g
Dakota Club Cab	4.7 V-8	5,100c,d
Dakota Club Cab	4.7 V-8	6,400a,c
Dakota Club Cab 4WD	3.9 V-6	3,800d,g
Dakota Club Cab 4WD	3.9 V-6	4,600a,g
Dakota Club Cab 4WD	3.9 V-6	5,000a,b
Dakota Club Cab 4WD	4.7 V-8	5,200d,g
Dakota Club Cab 4WD	4.7 V-8	6,200a,g
Dakota Club Cab 4WD	4.7 V-8	4,850b,d
Dakota Club Cab 4WD	4.7 V-8	6,150a,b
Dakota Quad Cab	3.9 V-6	3,250g,h
Dakota Quad Cab	3.9 V-6	3,750d,g
Dakota Quad Cab	3.9 V-6	4,550a,g
Dakota Quad Cab	3.9 V-6	4,500d,g
Dakota Quad Cab	3.9 V-6	4,900a,b
Dakota Quad Cab	4.7 V-8	5,150d,g
Dakota Quad Cab	4.7 V-8	6,150a,g
Dakota Quad Cab	4.7 V-8	4,800c,d
Dakota Quad Cab	4.7 V-8	6,100a,c
Dakota Quad Cab	5.9 V-8	4,750b,d
Dakota Quad Cab	5.9 V-8	6,350a,b
Dakota Quad Cab 4WD	3.9 V-6	3,450d,g
Dakota Quad Cab 4WD	3.9 V-6	4,250a,g
Dakota Quad Cab 4WD	3.9 V-6	4,650a,b
Dakota Quad Cab 4WD	4.7 V-8	4,900d,g
Dakota Quad Cab 4WD	4.7 V-8	5,900a,g
Dakota Quad Cab 4WD	4.7 V-8	4,800b,d
Dakota Quad Cab 4WD	4.7 V-8	5,800a,b
Dakota Quad Cab 4WD	5.9 V-8	4,500d,g
Dakota Quad Cab 4WD	5.9 V-8	6,100a,b
Dakota Quad Cab 4WD	4.7 V-8	4,750b,d
Durango	4.7 V-8	6,050a,b
Durango	5.2 V-8	4,700b,d
Durango	5.2 V-8	6,000a,b
Durango	5.9 V-8	5,950b,d
Durango	5.9 V-8	7,650a,b
Durango 4WD	4.7 V-8	4,450b,d
Durango 4WD	4.7 V-8	5,750a,b
Durango 4WD	5.9 V-8	5,650b,d
Durango 4WD	5.9 V-8	7,350a,b
Intrepid	All	2,000
Ram Van 1500:		
109/127" Wheelbase	3.9 V-6	8,800c,d
109" Wheelbase	5.2 V-8	10,000b,d
109" Wheelbase	5.2 V-8	10,500a,b
127" Wheelbase	5.2 V-8	11,500b,d
127" Wheelbase	5.2 V-8	12,500a,b
127" Wheelbase	5.9 V-8	12,000b,d

127" Wheelbase	5.9 V-8	13,000a,b
Ram Van 2500/3500:		
127" Wheelbase	5.2 V-8	12,500a,b
127" Wheelbase	5.2 V-8	13,000b,e
127" Wheelbase	5.9 V-8	13,000a,b
127" Wheelbase	5.9 V-8	13,500b,e

Ram Trucks:

1500	3.9 V-6	3,300b,d
1500	5.2 V-8	5,000d,g
1500 4WD	5.2 V-8	4,650d,g
1500	5.2/5.9 V-8	7,950a/d,b
1500 4WD	5.2 V-8	5,150a,g
1500 4WD	5.2 V-8	7,600a/d,b
1500 4WD	5.9 V-8	7,450a,b,d
1500 Club & Quad Cab	5.2 V-8	4,650g,i
1500 Club & Quad Cab	5.2/5.9 V-8	7,650b,j
1500 Club & Quad Cab 4WD	5.2 V-8	4,300d,g
1500 Club & Quad Cab 4WD	5.2 V-8	4,800a,g
1500 Club & Quad Cab 4WD	5.2/5.9 V-8	7,250b,j
2500	5.9 V-8	8,800f,g
2500	5.9 V-8	8,900b,f
2500	5.9 TD	14,150f,i
2500	5.9 TD	10,200b,d
2500	5.9 TD	12,200b,e
2500	8.0 V-10	13,350f,g
2500	8.0 V-10	13,400b,f
2500 4WD	5.9 V-8	8,350f,g
2500 4WD	5.9 V-8	8,400b,f
2500 4WD	5.9 TD	13,700f,i
2500 4WD	5.9 TD	9,750b,d
2500 4WD	5.9 TD	11,750b,e
2500 4WD	8.0 V-10	12,950f,g
2500 4WD	8.0 V-10	13,000b,f
2500 Club & Quad Cab	5.9 V-8	8,500g,f
2500 Club & Quad Cab	5.9 V-8	8,600b,f
2500 Club & Quad Cab	5.9 TD	13,850f,i
2500 Club & Quad Cab	5.9 TD	9,900b,d
2500 Club & Quad Cab	5.9 TD	11,900b,e
2500 Club & Quad Cab	8.0 V-10	13,150f,g
2500 Club & Quad Cab	8.0 V-10	13,200b,f
2500 Club & Quad Cab 4WD	5.9 V-8	8,050f,g
2500 Club & Quad Cab 4WD	5.9 V-8	8,150b,f
2500 Club & Quad Cab 4WD	5.9 TD	9,400d,i
2500 Club & Quad Cab 4WD	5.9 TD	11,400e,i
2500 Club & Quad Cab 4WD	5.9 TD	9,450b,d
2500 Club & Quad Cab 4WD	5.9 TD	11,450b,e
2500 Club & Quad Cab 4WD	8.0 V-10	12,650g,f
2500 Club & Quad Cab 4WD	8.0 V-10	12,700b,f
350		

F-250/F-350 Super Duty, Automatic Transmission,

Conventional Towing:

F-250	5.4 V-8	8,100d
F-250 4WD	5.4 V-8	7,600d
F-250	5.4 V-8	9,600e
F-250 4WD	5.4 V-8	9,100e
F-250 All Models	6.8 V-10	10,000d/j
F-250 All Models	7.3 TD	10,000d
F-350	5.4 V-8	8,000d
F-350 DRW	5.4 V-8	7,800d
F-350	5.4 V-8	9,500e
F-350 DRW	5.4 V-8	9,300e
F-350 4WD	5.4 V-8	7,600d
F-350 4WD DRW	5.4 V-8	7,300d
F-350 4WD	5.4 V-8	9,100e
F-350 4WD DRW	5.4 V-8	8,800e
F-350 All Models	6.8 V-10	10,000d/j
F-350 All Models	7.3 TD	10,000d/e
F-250 SuperCab	5.4 V-8	7,700d
F-250 SuperCab 4WD	5.4 V-8	7,300d
F-250 SuperCab	5.4 V-8	9,200e
F-250 SuperCab 4WD	5.4 V-8	8,800e
F-350 SuperCab	5.4 V-8	7,700d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab 4WD	5.4 V-8	7,300d
F-350 SuperCab 4WD DRW	5.4 V-8	7,100d
F-350 SuperCab	5.4 V-8	9,200e
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab 4WD	5.4 V-8	8,800e
F-350 SuperCab 4WD DRW	5.4 V-8	8,600e
F-250 Crew Cab	5.4 V-8	7,400d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 Crew Cab	5.4 V-8	8,900e
F-250 Crew Cab 4WD	5.4 V-8	8,600e

F-250/F-350 Super Duty, Manual Transmission,

Fifth-Wheel Towing:

F-250	5.4 V-8	8,200d
F-250 4WD	5.4 V-8	7,700d
F-350	5.4 V-8	8,100d
F-350 DRW	5.4 V-8	7,800d
F-350 4WD	5.4 V-8	7,700d
F-350 4WD DRW	5.4 V-8	7,400d
F-250	5.4 V-8	9,700e
F-250 4WD	5.4 V-8	9,200e
F-350	5.4 V-8	9,600e
F-350 DRW	5.4 V-8	9,300e
F-350 4WD	5.4 V-8	9,200e
F-350 4WD DRW	5.4 V-8	8,900e
F-250	6.8 V-10	11,000d
F-250 4WD	6.8 V-10	10,500d
F-350	6.8 V-10	10,900d
F-350 DRW	6.8 V-10	10,600d
F-350 4WD	6.8 V-10	10,500d
F-350 4WD DRW	6.8 V-10	10,200d
F-250	6.8 V-10	14,500j
F-250 4WD	6.8 V-10	14,000j
F-350	6.8 V-10	14,400j
F-350 DRW	6.8 V-10	14,100j
F-350 4WD	6.8 V-10	14,000j
F-350 4WD DRW	6.8 V-10	13,700j
F-250	7.3 TD	14,000d
F-250 4WD	7.3 TD	13,500d
F-350	7.3 TD	13,900d
F-350 DRW	7.3 TD	13,600d/e
F-350 4WD	7.3 TD	13,500d
F-350 4WD DRW	7.3 TD	13,100d/e
F-250 SuperCab	5.4 V-8	7,800d
F-250 SuperCab 4WD	5.4 V-8	7,400d
F-250 Crew Cab	5.4 V-8	7,500d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 SuperCab	5.4 V-8	9,300d
F-250 SuperCab 4WD	5.4 V-8	8,900e
F-250 Crew Cab	5.4 V-8	9,000e
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-250 SuperCab	6.8 V-10	10,600d
F-250 SuperCab 4WD	6.8 V-10	10,200d
F-250 Crew Cab	6.8 V-10	10,300d
F-250 Crew Cab 4WD	6.8 V-10	10,000d
F-250 SuperCab	6.8 V-10	14,100j
F-250 SuperCab 4WD	6.8 V-10	13,700j
F-250 Crew Cab	6.8 V-10	13,800j
F-250 Crew Cab 4WD	6.8 V-10	13,500j
F-250 SuperCab	7.3 TD	13,600d
F-250 SuperCab 4WD	7.3 TD	13,200d
F-250 Crew Cab	7.3 TD	13,300d
F-250 Crew Cab 4WD	7.3 TD	12,900d
F-350 SuperCab	5.4 V-8	7,800d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab 4WD	5.4 V-8	7,500d
F-350 SuperCab 4WD	5.4 V-8	7,400d

F-350 SuperCab 4WD DRW

5.4 V-8	7,200d	
F-350 Crew Cab	5.4 V-8	7,500d
F-350 Crew Cab 4WD	5.4 V-8	7,100d
F-350 SuperCab	5.4 V-8	9,300e
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab 4WD	5.4 V-8	8,900e
F-350 SuperCab 4WD DRW	5.4 V-8	8,700e
F-350 Crew Cab	5.4 V-8	8,900e
F-350 Crew Cab 4WD	5.4 V-8	8,600e
F-350 SuperCab	6.8 V-10	10,600d
F-350 SuperCab DRW	6.8 V-10	10,300d
F-350 SuperCab 4WD	6.8 V-10	10,200d
F-350 SuperCab 4WD DRW	6.8 V-10	10,000d
F-350 Crew Cab	6.8 V-10	10,300d
F-350 Crew Cab DRW	6.8 V-10	10,000d
F-350 Crew Cab 4WD	6.8 V-10	10,000d
F-350 Crew Cab 4WD DRW	6.8 V-10	9,600d
F-350 SuperCab	6.8 V-10	14,100j
F-350 SuperCab DRW	6.8 V-10	13,800j
F-350 SuperCab 4WD	6.8 V-10	13,700j
F-350 SuperCab 4WD DRW	6.8 V-10	13,500j
F-350 Crew Cab	6.8 V-10	13,800j
F-350 Crew Cab DRW	6.8 V-10	13,500j
F-350 Crew Cab 4WD	6.8 V-10	13,500j
F-350 Crew Cab 4WD DRW	6.8 V-10	13,100j
F-350 SuperCab	7.3 TD	13,600d
F-350 SuperCab DRW	7.3 TD	13,300d/e
F-350 SuperCab 4WD	7.3 TD	13,200d
F-350 SuperCab 4WD DRW	7.3 TD	12,900d/e
F-350 Crew Cab	7.3 TD	13,300d
F-350 Crew Cab DRW	7.3 TD	13,000d/e
F-350 Crew Cab 4WD	7.3 TD	13,000d
F-350 Crew Cab 4WD DRW	7.3 TD	12,600d/e

F-250/F-350 Super Duty, Automatic Transmission,

Fifth-Wheel Towing:

F-250	5.4 V-8	8,100d
F-250 4WD	5.4 V-8	7,600d
F-350	5.4 V-8	8,000d
F-350 DRW	5.4 V-8	7,800d
F-350 4WD	5.4 V-8	7,600d
F-350 4WD DRW	5.4 V-8	7,300d
F-250	5.4 V-8	9,600e
F-250 4WD	5.4 V-8	9,100e
F-350	5.4 V-8	9,500e
F-350 DRW	5.4 V-8	9,300e
F-350 4WD	5.4 V-8	9,100e
F-350 4WD DRW	5.4 V-8	8,800e
F-250	6.8 V-10	11,500d
F-250 4WD	6.8 V-10	11,000d
F-350	6.8 V-10	11,400d
F-350 DRW	6.8 V-10	11,100d
F-350 4WD	6.8 V-10	11,000d
F-250 4WD DRW	6.8 V-10	10,600d
F-250	6.8 V-10	14,500j
F-250 4WD	6.8 V-10	14,000j
F-350	6.8 V-10	14,400j
F-350 DRW	6.8 V-10	14,100j
F-350 4WD	6.8 V-10	14,000j
F-250 4WD DRW	6.8 V-10	13,600j
F-250	7.3 TD	14,000d
F-250 4WD	7.3 TD	13,500d
F-350	7.3 TD	13,900d
F-350 DRW	7.3 TD	13,600d/e
F-350 4WD	7.3 TD	13,500d
F-350 4WD DRW	7.3 TD	13,100d/e
F-250 SuperCab	5.4 V-8	7,700d
F-250 SuperCab 4WD	5.4 V-8	7,300d
F-250 Crew Cab	5.4 V-8	7,400d
F-250 Crew Cab 4WD	5.4 V-8	7,100d
F-250 SuperCab	5.4 V-8	9,200e
F-250 SuperCab 4WD	5.4 V-8	8,800e
F-250 Crew Cab	5.4 V-8	8,900e
F-250 Crew Cab 4WD	5.4 V-8	8,600e
F-250 SuperCab	6.8 V-10	11,100d
F-250 SuperCab 4WD	6.8 V-10	10,700d
F-250 Crew Cab	6.8 V-10	10,800d
F-250 Crew Cab 4WD	6.8 V-10	10,400d
F-250 SuperCab	6.8 V-10	14,100j
F-250 SuperCab 4WD	6.8 V-10	13,700j
F-250 Crew Cab	6.8 V-10	13,800j
F-250 Crew Cab 4WD	6.8 V-10	13,400j
F-250 SuperCab	7.3 TD	13,700d
F-250 Crew Cab 4WD	7.3 TD	13,200d
F-250 Crew Cab	7.3 TD	13,400d
F-250 Crew Cab 4WD	7.3 TD	13,000d
F-350 SuperCab	5.4 V-8	7,700d
F-350 SuperCab DRW	5.4 V-8	7,500d
F-350 SuperCab 4WD	5.4 V-8	7,300d
F-350 SuperCab 4WD DRW	5.4 V-8	7,100d
F-350 Crew Cab	5.4 V-8	7,400d

F-350 Crew Cab 4WD

5.4 V-8	7,100d	
F-350 SuperCab	5.4 V-8	9,200e
F-350 SuperCab DRW	5.4 V-8	9,000e
F-350 SuperCab 4WD	5.4 V-8	8,800e
F-350 SuperCab 4WD DRW	5.4 V-8	8,600e
F-350 Crew Cab	5.4 V-8	8,900e
F-350 Crew Cab 4WD	5.4 V-8	8,600e
F-350 SuperCab	6.8 V-10	11,100d
F-350 SuperCab DRW	6.8 V-10	10,800d
F-350 SuperCab 4WD	6.8 V-10	10,700d
F-350 SuperCab 4WD DRW	6.8 V-10	10,400d
F-350 Crew Cab	6.8 V-10	10,800d
F-350 Crew Cab DRW	6.8 V-10	10,500d
F-350 Crew Cab 4WD	6.8 V-10	10,400d
F-350 Crew Cab 4WD DRW	6.8 V-10	10,000a,k
F-350 SuperCab	6.8 V-10	14,100j
F-350 SuperCab DRW	6.8 V-10	13,800j
F-350 SuperCab 4WD	6.8 V-10	13,700j
F-350 SuperCab 4WD DRW	6.8 V-10	13,400j
F-350 Crew Cab	6.8 V-10	13,800j
F-350 Crew Cab DRW	6.8 V-10	13,500j
F-350 Crew Cab 4WD	6.8 V-10	13,400j
F-350 Crew Cab 4WD DRW	6.8 V-10	13,000j
F-350 SuperCab	7.3 TD	13,600d
F-350 SuperCab DRW	7.3 TD	13,300d/e
F-350 SuperCab 4WD	7.3 TD	13,200d
F-350 SuperCab 4WD DRW	7.3 TD	12,900d/e
F-350 Crew Cab	7.3 TD	13,300d
F-350 Crew Cab DRW	7.3 TD	13,000d/e
F-350 Crew Cab 4WD	7.3 TD	13,000d
F-350 Crew Cab 4WD DRW	7.3 TD	12,600d/e

F-450/F-550 Super Duty, Manual Transmission,

Fifth-Wheel Towing:

F-450	6.8 V-10	14,700k,l
F-450 4WD	6.8 V-10	14,400k,l
F-450	7.3 TD	18,200k
F-450 4WD	7.3 TD	17,900k
F-550	7.3 TD	18,100k
F-550 4WD	7.3 TD	17,800k
F-450 Crew Cab	6.8 V-10	14,200k,l
F-450 Crew Cab 4WD	6.8 V-10	13,800k,l
F-450 Crew Cab	7.3 TD	17,600k
F-450 Crew Cab 4WD	7.3 TD	17,300k
F-550 Crew Cab	7.3 TD	17,500k
F-550 Crew Cab 4WD	7.3 TD	17,200k

F-450/F-550 Super Duty, Automatic Transmission,

Fifth-Wheel Towing:

F-450	6.8 V-10	16,700k
F-450 4WD	6.8 V-10	16,400k
F-450	6.8 V-10	18,700l
F-450 4WD	6.8 V-10	18,400l
F-550 4WD	6.8 V-10	16,600k
F-550 4WD	6.8 V-10	16,300k
F-550	6.8 V-10	18,600l
F-550 4WD	6.8 V-10	18,300l
F-450	7.3 TD	18,200k
F-450 4WD	7.3 TD	17,900k
F-550	7.3 TD	18,100k
F-550 4WD	7.3 TD	17,800k
F-450 Crew Cab	6.8 V-10	16,100k
F-450 Crew Cab 4WD	6.8 V-10	15,800k
F-550 Crew Cab	6.8 V-10	16,000k
F-550 Crew Cab 4WD	6.8 V-10	15,700k
F-450 Crew Cab	6.8 V-10	18,100l
F-450 Crew Cab 4WD	6.8 V-10	17,800l
F-550 Crew Cab	6.8 V-10	18,600l
F-550 Crew Cab 4WD	6.8 V-10	17,700l
F-450 Crew Cab	7.3 TD	17,600k
F-450 Crew Cab 4WD	7.3 TD	17,300k
F-550 Crew Cab	7.3 TD	17,600k
F-550 Crew Cab 4WD	7.3 TD	17,200k

Ranger, Automatic Transmission:

Ranger	2.5 I-4	2,180e
Ranger	3.0 V-6	4,120e
Ranger 4WD	3.0 V-6	3,860d
Ranger 4WD	3.0 V-6	4,360e
Ranger SuperCab 4WD	3.0 V-6	3,660d
Ranger SuperCab 4WD	3.0 V-6	4,160e
Ranger	4.0 V-6	6,060c
Ranger SuperCab	4.0 V-6	5,860c
Ranger 4WD	4.0 V-6	5,800d/e
Ranger SuperCab 4WD	4.0 V-6	5,620d/e

Ranger, Manual Transmission:

Ranger	3.0 V-6	2,660d
Ranger 4WD	3.0 V-6	2,400d/e
Ranger SuperCab	3.0 V-6	2,460d/e
Ranger SuperCab 4WD	3.0 V-6	2,200d/e
Ranger 4WD	4.0 V-6	3,340d/e
Ranger SuperCab 4WD	4.0 V-6	3,160d/e

Ranger

Ranger SuperCab

4.0 V-6	3,600c
4.0 V-6	3,400c

Windstar:

Windstar	3.0 V-6	2,000e
Windstar	3.8 V-6	3,500a

TD = Turbodiesel

- aRequires 3.08:1 axle ratio.
- bRequires 3.31:1 axle ratio.
- cRequires 3.55:1 axle ratio.
- dRequires 3.73:1 axle ratio.
- eRequires 3.98/4.09/4.10:1 axle ratio.
- fMust be equipped with heavy-duty towing package.
- gRequires 16-inch wheel option.
- hRequires 17-inch wheel option.
- iRequires 3.27:1 axle ratio.
- jRequires 4.30:1 axle ratio.
- kRequires 4.88:1 axle ratio.
- lRequires 5.38:1 axle ratio.

HONDA

Vehicle	Engine	Tow Limit (lbs.)
Odyssey	V-6 24-valve	3,500a,b
Passport	3.2 V-6	4,500
Acura RL	3.5	2,000

aWith transmission fluid cooler and two occupants. Deduct 150 pounds per passenger up to seven passengers.

bWithout transmission cooler: 2,000 pounds maximum with two occupants.

HYUNDAI

Vehicle	Engine	Tow Limit (lbs.)
Sonata	V	